

NEW ZEALAND CIVIL AIRWORTHINESS REQUIREMENTS
VOLUME 2
AIRWORTHINESS DIRECTIVES

SECTION A
GLIDERS VLIEGTUIGBOUW NV SAGITTA AD SCHEDULE

In addition to the ADs scheduled below, relevant ADs in the 'AIRCRAFT GENERAL' AD Schedule and any other relevant ADs in Section C 'COMPONENTS AND EQUIPMENT' shall be complied with

DCA/SAG/1 Rudder Pedal Stops - Modification

Applicability: Model 013 S/N 001 through 012

Requirement: Netherlands AD 65-08-27

Compliance: At C of A

Effective Date: 31 August 1970

Note: A copy of the reference document may be obtained from the Director

DCA/SAG/2 Wing Spar - Modification

Applicability: All models

Requirement: Airepair Ltd Modification AIRP-M-39

Compliance: As detailed

Effective Date: 31 August 1970

**DCA/SAG/3 Temporary Operating Limitations Placard -
Modification**

Applicability: All models

Requirement: Netherlands AD 72-34-00

Compliance: Before further flight

Effective Date: 31 July 1972

Note: A copy of the reference document may be obtained from the Director

DCA/SAG/4 Aileron Hinges - Inspection

Applicability: All model 013

Requirement: To preclude possibility of aileron hinge failure, accomplish the following: Dismantle aileron hinge; inspect for corrosion and cracking particularly in area of 'dimpled' holes. Renew or rectify defective assemblies and protect against corrosion. (Netherlands AD 81-58-57 refers)

Compliance: 30 November 1981

Effective Date: 16 October 1981

